

Dimensions

Imperial	SR-210
Empty Weight	68 lb
Overall Length	22"
Overall Height	32"
Overall Width	30"
Hopper Length	22"
Hopper Width	30"

Metric	SR-210
Empty Weight	30.8 kg
Overall Length	55.9 cm
Overall Height	81.3 cm
Overall Width	76.2 cm
Hopper Length	55.9 cm
Hopper Width	76.2 cm

Operational

Imperial	SR-210
Capacity (Volume)	3.0 cu ft
Capacity (Weight)	240 lb
Spreading Width	Up to 25'

Metric	SR-210
Capacity (Volume)	0.085 cu m
Capacity (Weight)	108.9 kg
Spreading Width	Up to 7.6 m

Electrical

Imperial	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Metric	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Construction

Imperial	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin
Auger	3" vertical high-flow auger
Mounting	2" receiver hitch is standard

Metric	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin
Auger	7.6 cm vertical high-flow auger
Mounting	5.1 cm receiver hitch is standard

Standard Equipment

Imperial	SR-210
Cover	Optional

Metric	SR-210
Cover	Optional