

**Dimensions**

<b>Imperial</b>	<b>SD-600-1</b>
Empty Weight	175 lb
Overall Length	24"
Overall Height	28"
Overall Width	49½"
Hopper Length	20¼"
Hopper Width	48"

<b>Metric</b>	<b>SD-600-1</b>
Empty Weight	79.4 kg
Overall Length	61.0 cm
Overall Height	71.1 cm
Overall Width	125.7 cm
Hopper Length	51.4 cm
Hopper Width	121.9 cm

**Operational**

<b>Imperial</b>	<b>SD-600-1</b>
Capacity (Volume)	6.0 cu ft
Capacity (Weight)	480 lb
Spreading Width	36"

<b>Metric</b>	<b>SD-600-1</b>
Capacity (Volume)	0.169 cu m
Capacity (Weight)	217.7 kg
Spreading Width	91.4 cm

**Electrical**

<b>Imperial</b>	<b>SD-600-1</b>
Speed Control	Digital, self-diagnosing variable-speed control
Wiring Harness	Completely loomed with molded plugs

<b>Metric</b>	<b>SD-600-1</b>
Speed Control	Digital, self-diagnosing variable-speed control
Wiring Harness	Completely loomed with molded plugs

**Construction**

<b>Imperial</b>	<b>SD-600-1</b>
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Mounting	Mount not included. (Receiver, 3-point or Utility mount optional)

<b>Metric</b>	<b>SD-600-1</b>
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Mounting	Mount not included. (Receiver, 3-point or Utility mount optional)

**Standard Equipment**

<b>Imperial</b>	<b>SD-600-1</b>
Top Screen	1/4" steel rod construction with grid pattern
Cover	Fitted lid
Vibrator	Standard
Inverted	Patented vibrating baffle to maximize material flow

<b>Metric</b>	<b>SD-600-1</b>
Top Screen	0.6 cm steel rod construction with grid pattern
Cover	Fitted lid
Vibrator	Standard
Inverted	Patented vibrating baffle to maximize material flow